




Specifications	
Precision grade	KHK W 001 grade 2
Reference section of gear	Axial
Gear teeth	Standard full depth
Normal pressure angle	20°
Material	SCM440
Heat treatment	Thermal refined, tooth surface induction hardened
Tooth hardness	50 ~ 60HRC



W5


Catalog No.	Axial module	Number of starts	Lead angle	Hand thread	Shape	Total length		Neck length (L)	Face width	Neck length (R)	Shaft length (R)	Pitch dia.
						J	K					
KWG0.5-R1	m0.5	1	3°11'	R	W5	65	19	—	12	—	34	9
KWG0.5-R2		2	6°20'	R	W5	65	19	—	12	—	34	9
KWG0.8-R1	m0.8	1	3°49'	R	W5	85	25	—	20	—	40	12
KWG0.8-R2		2	7°36'	R	W5	85	25	—	20	—	40	12

[Caution on Product Characteristics] ① These worms produce axial thrust forces. See Page 344 for more details.

* For products not categorized in our KHK Stock Gear series, custom gear production services with **short lead times** is available. For details see Page 8.



Specifications	
Precision grade	KHK W 002 grade 2
Reference section of gear	Rotating plane
Gear teeth	Standard full depth
Normal pressure angle	20°
Material	CAC702 (formerly JIS A2/BC2)
Heat treatment	—
Tooth hardness	—



HA

Catalog No.	Reduction ratio	Transverse module	No. of teeth	Number of starts	Helix angle	Hand thread	Shape	Bore		Pitch dia.	Throat dia.	Outside dia.	Face width
								A _{H7}	B				
AG0.5-20R1	20	m0.5	20	1	3°11'	R	HA	4	9	10	—	11	5
AG0.5-20R2	10		20	2	6°20'	R	HA	4	9	10	—	11	5
AG0.5-30R1	30		30	1	3°11'	R	HA	4	12	15	—	16	5
AG0.5-30R2	15		30	2	6°20'	R	HA	4	12	15	—	16	5
AG0.5-40R1	40		40	1	3°11'	R	HA	5	15	20	—	21	5
AG0.5-50R1	50	m0.5	50	1	3°11'	R	HA	5	20	25	—	26	5
AG0.5-60R1	60		60	1	3°11'	R	HA	5	25	30	—	31	5
AG0.8-20R1	20	m0.8	20	1	3°49'	R	HA	5	12	16	—	17.6	8
AG0.8-20R2	10		20	2	7°36'	R	HA	5	12	16	—	17.6	8
AG0.8-30R1	30		30	1	3°49'	R	HA	5	18	24	—	25.6	8
AG0.8-30R2	15		30	2	7°36'	R	HA	5	18	24	—	25.6	8
AG0.8-40R1	40		40	1	3°49'	R	HA	6	20	32	—	33.6	8
AG0.8-50R1	50	m0.8	50	1	3°49'	R	HA	8	25	40	—	41.6	8
AG0.8-60R1	60		60	1	3°49'	R	HA	8	25	48	—	49.6	8

[Caution on Product Characteristics] ① The allowable torques shown in the table are the calculated values according to the assumed usage conditions. Please see Page 342 for more details.

Outside dia.	Neck dia.	Shaft dia.	Weight (kg)	Catalog No.
Q	R	S _{H7}		
10	—	6	0.018	KWG0.5-R1
10	—	6	0.018	KWG0.5-R2
13.6	—	8	0.043	KWG0.8-R1
13.6	—	8	0.043	KWG0.8-R2

[Caution on Secondary Operations] ① Please read "Caution on Performing Secondary Operations" (Page 344) when performing modifications and/or secondary operations for safety concerns. KHK Quick-Mod Gears, the KHK's system for quick modification of KHK stock gears is also available.
② Due to the gear teeth being induction hardened, no secondary operations can be performed on tooth areas including the bottom land (approx. 2 to 3 mm). Use carbide tools for the modification of the shaft area near the bottom land.



NOTE 1: Allowable torque for worm revolution (rpm)


Hub width	Total length	Web thickness (H)	Web O.D. (I)	Mounting distance J	Allowable torque (N·m) NOTE 1								Backlash (mm)	Weight (kg)	Catalog No.
					30 rpm	100 rpm	300 rpm	600 rpm	900 rpm	1200 rpm	1800 rpm				
7	12	—	—	9.5	0.52	0.44	0.36	0.30	0.26	0.24	0.21	0.02~0.14	0.0056	AG0.5-20R1	
7	12	—	—	9.5	0.51	0.42	0.33	0.27	0.24	0.22	0.19	0.02~0.14	0.0056	AG0.5-20R2	
7	12	—	—	12	1.09	0.94	0.77	0.65	0.58	0.53	0.48	0.02~0.14	0.012	AG0.5-30R1	
7	12	—	—	12	1.09	0.92	0.73	0.60	0.54	0.49	0.43	0.02~0.14	0.012	AG0.5-30R2	
7	12	—	—	14.5	1.86	1.60	1.34	1.15	1.02	0.94	0.84	0.02~0.14	0.020	AG0.5-40R1	
7	12	—	—	17	2.82	2.42	2.05	1.77	1.58	1.46	1.30	0.02~0.14	0.035	AG0.5-50R1	
7	12	—	—	19.5	3.94	3.41	2.89	2.50	2.26	2.08	1.87	0.02~0.14	0.053	AG0.5-60R1	
8	16	—	—	14	1.78	1.50	1.21	1.00	0.88	0.82	0.71	0.06~0.17	0.018	AG0.8-20R1	
8	16	—	—	14	1.76	1.44	1.11	0.91	0.80	0.74	0.63	0.06~0.17	0.018	AG0.8-20R2	
8	16	—	—	18	3.77	3.21	2.62	2.20	1.96	1.81	1.61	0.06~0.17	0.043	AG0.8-30R1	
8	16	—	—	18	3.75	3.14	2.46	2.02	1.80	1.65	1.45	0.06~0.17	0.043	AG0.8-30R2	
8	16	—	—	22	6.45	5.49	4.55	3.87	3.46	3.19	2.83	0.06~0.17	0.068	AG0.8-40R1	
8	16	—	—	26	9.75	8.31	6.94	5.94	5.34	4.96	4.38	0.06~0.17	0.10	AG0.8-50R1	
8	16	—	—	30	13.6	11.7	9.77	8.39	7.63	7.05	6.27	0.06~0.17	0.14	AG0.8-60R1	

[Caution on Secondary Operations] ① Please read "Caution on Performing Secondary Operations" (Page 344) when performing modifications and/or secondary operations for safety concerns. KHK Quick-Mod Gears, the KHK's system for quick modification of KHK stock gears is also available.

KWG Ground Worm Shafts

Module 5, 6

Specifications	
Precision grade	KHK W 001 grade 2
Reference section of gear	Axial
Gear teeth	Standard full depth
Normal pressure angle	20°
Material	SCM440
Heat treatment	Thermal refined, tooth surface induction hardened
Tooth hardness	50 ~ 60HRC



W6

Catalog No.	Axial module	Number of starts	Lead angle	Hand thread	Shape	Total length						Pitch dia.
						J	K	L	M	N	O	
KWG5-R1	m5	1	5°43'	R	W6	400	75	30	90	30	175	50
KWG6-R1	m6	1	5°43'	R	W6	400	60	40	100	40	160	60

[Caution on Product Characteristics] ① These worms produce axial thrust forces. See Page 344 for more details.

* For products not categorized in our KHK Stock Gear series, custom gear production services with **short lead times** is available. For details see Page 8.

Ground Worm Shafts


Outside dia.	Neck dia.	Shaft dia.	Weight (kg)	Catalog No.
Q	R	S		
60	36	50.2	5.75	KWG5-R1
72	44	60.2	8.09	KWG6-R1

[Caution on Secondary Operations] ① Please read "Caution on Performing Secondary Operations" (Page 344) when performing modifications and/or secondary operations for safety concerns. KHK Quick-Mod Gears, the KHK's system for quick modification of KHK stock gears is also available.
② Due to the gear teeth being induction hardened, no secondary operations can be performed on tooth areas including the bottom land (approx. 2 to 3 mm). Use carbide tools for the modification of the shaft area near the bottom land.

AGF Worm Wheels

Module 5, 6

Specifications	
Precision grade	KHK W 002 grade 2
Reference section of gear	Rotating plane
Gear teeth	Standard full depth
Normal pressure angle	20°
Material	CAC702 (formerly JIS A&BC2) *
Heat treatment	—
Tooth hardness	—




H6

* H8, H9 shape have a hub made from FC200 cast iron.

Catalog No.	Reduction ratio	Transverse module	No. of teeth	Number of starts	Profile shift coefficient	Helix angle	Hand thread	Shape	Bore		Pitch dia.	Throat dia.	Outside dia.	Face width	Hub width(F)
									A _{H7}	B					
AGF5-20R1	20	m5	20	1	0	5°43'	R	H6	22	75	100	110	115	35	23
AGF5-25R1	25		25	1	0	5°43'	R	H6	22	75	125	135	140	35	23
AGF5-30R1	30		30	1	0	5°43'	R	H8	22	75	150	160	165	35	23
AGF5-36R1	36		36	1	0	5°43'	R	H9	22	90	180	190	195	35	23
AGF5-40R1	40		40	1	0	5°43'	R	H9	22	110	200	210	215	35	23
AGF5-48R1	48	48	1	0	5°43'	R	H0	140	—	240	250	255	35	7.5	
AGF5-50R1	50	50	1	0	5°43'	R	H0	150	—	250	260	265	35	7.5	
AGF5-60R1	60	60	1	0	5°43'	R	H0	200	—	300	310	315	35	7.5	
AGF6-20R1	20	m6	20	1	0	5°43'	R	H6	25	85	120	132	138	40	23
AGF6-25R1	25		25	1	0	5°43'	R	H6	25	90	150	162	168	40	23
AGF6-30R1	30		30	1	0	5°43'	R	H8	25	100	180	192	198	40	23
AGF6-36R1	36		36	1	0	5°43'	R	H9	25	110	216	228	234	40	23
AGF6-40R1	40		40	1	0	5°43'	R	H0	130	—	240	252	258	40	8
AGF6-48R1	48	48	1	0	5°43'	R	H0	180	—	288	300	306	40	8	
AGF6-50R1	50	50	1	0	5°43'	R	H0	190	—	300	312	318	40	8	
AGF6-60R1	60	60	1	0	5°43'	R	H0	250	—	360	372	378	40	8	

[Caution on Product Characteristics] ① The allowable torques shown in the table are the calculated values according to the assumed usage conditions. Please see Page 342 for more details.
② There may be space in the casting between the two materials, but it will not affect the joint strength.
③ For H0-shaped products with a bore size of ϕ 190 or more, the bore tolerance is H8.

Worm Wheels



* CS has a sand mold casting finish.

NOTE 1 : Allowable torque for worm revolution (rpm)

Hub width (L)	Total length	Web thickness (H)	Web O.D. (I)	Mounting distance	Allowable torque (N-m) <small>NOTE 1</small>						Backlash (mm)	Weight (kg)	Catalog No.	
					30 rpm	100 rpm	300 rpm	600 rpm	900 rpm	1200 rpm				1800 rpm
F'	G			J										
12	70	—	—	75	211	172	134	108	95.0	86.2	72.7	0.22~0.35	3.26	AGF5-20R1
12	70	—	—	87.5	319	261	206	168	147	134	114	0.22~0.35	4.48	AGF5-25R1
12	70	(25)	(115)	100	446	369	291	239	211	191	164	0.22~0.35	5.37	AGF5-30R1
12	70	(25)	(140)	115	627	519	414	343	302	274	234	0.22~0.35	7.70	AGF5-36R1
12	70	(26)	(162)	125	763	632	506	421	371	337	288	0.22~0.35	9.97	AGF5-40R1
17.5	35	10	195	145	1070	886	715	598	530	483	411	0.22~0.35	5.04	AGF5-48R1
17.5	35	10	205	150	1150	956	772	646	574	523	446	0.22~0.35	5.28	AGF5-50R1
17.5	35	10	255	175	1610	1340	1090	913	820	744	639	0.22~0.35	6.48	AGF5-60R1
12	75	—	—	90	329	268	208	167	146	131	110	0.24~0.37	4.95	AGF6-20R1
12	75	—	—	105	497	405	319	259	227	204	173	0.24~0.37	7.14	AGF6-25R1
12	75	(30)	(135)	120	696	572	451	368	325	290	248	0.24~0.37	9.21	AGF6-30R1
12	75	(30)	(172)	138	978	806	641	528	466	417	355	0.24~0.37	12.5	AGF6-36R1
20	40	12	190	150	1190	981	784	648	572	513	436	0.24~0.37	6.20	AGF6-40R1
20	40	12	240	174	1670	1380	1110	920	816	735	628	0.24~0.37	7.58	AGF6-48R1
20	40	12	250	180	1800	1480	1200	994	885	796	676	0.24~0.37	8.00	AGF6-50R1
20	40	12	310	210	2520	2090	1680	1410	1260	1130	969	0.24~0.37	10.0	AGF6-60R1

[Caution on Secondary Operations] ① Please read "Caution on Performing Secondary Operations" (Page 344) when performing modifications and/or secondary operations for safety concerns. KHK Quick-Mod Gears, the KHK's system for quick modification of KHK stock gears is also available.
② The tooth and the hub areas, fastened by casting, are designed to have higher hardness than other parts of the gear. However, please avoid areas other than the hub. Also, the strength may decrease if secondary operations are performed.